

3m x62w manual



File Name: 3m x62w manual.pdf

Size: 1875 KB

Type: PDF, ePub, eBook

Category: Book

Uploaded: 7 May 2019, 18:52 PM

Rating: 4.6/5 from 680 votes.

Status: AVAILABLE

Last checked: 16 Minutes ago!

In order to read or download 3m x62w manual ebook, you need to create a FREE account.

[**Download Now!**](#)

eBook includes PDF, ePub and Kindle version

[Register a free 1 month Trial Account.](#)

[Download as many books as you like \(Personal use\)](#)

[Cancel the membership at any time if not satisfied.](#)

[Join Over 80000 Happy Readers](#)

Book Descriptions:

We have made it easy for you to find a PDF Ebooks without any digging. And by having access to our ebooks online or by storing it on your computer, you have convenient answers with 3m x62w manual . To get started finding 3m x62w manual , you are right to find our website which has a comprehensive collection of manuals listed.

Our library is the biggest of these that have literally hundreds of thousands of different products represented.



Book Descriptions:

3m x62w manual

The meanings of these symbols are Contact immediately your dealer if anything is missing. For moving the projector, be sure to use the original packing materials. Preparations Preparations Fastening the lens cover To avoid losing the lens cover, please fasten it the lens cap to the projector using the strap. Strap ring Strap. Under certain exceptional circumstances, the projector may not operate correctly and the microprocessor will need to be reset. In such a case, please push the Restart switch by using a cocktail stick or similar, and before turning on again, make the projector cool down at least 10 minutes without operating. Use the RGB button or VIDEO button on remote control to change the input port. When the projector menu is displayed, you can change the input port by INPUT button. The adjustment range of the elevator feet is 0 to 9 degrees. It is intended to be used as an extra theft prevention measure. A commercial antitheft chain or wire can be attached to the security bar on the projector. How to attach An antitheft chain or wire can be attached as shown in the illustration. Then the resolution will go back to the original. To change the settings, refer to the AUDIO item in the SETUP menu. . To change the settings, refer to the AUDIO item in the SETUP menu. If it is damaged, contact your dealer to newly get correct one. Neglect could shorten the lifetime of the lamp. If no input is detected at the port, the projector will check the RGB IN2 port. When an input is found, the projector will stop searching and display the image. If no signal is found, the projector will return to the state selected before the operation. Do not leave the projector in the FREEZE mode for too long. BRIGHTNESS See the item BRIGHTNESS in the PICTURE menu 29. This is not a malfunction. If you want to adjust the 2nd tone from left end on the test pattern Gray scale of 9 steps, use the equalizing adjustment bar "1". This is not a malfunction. This is not a malfunction. <http://abc-tel.ru/data/comcast-motorola-hd-dvr-manual.xml>

- **3m x62w manual, 3m x62w manual pdf, 3m x62w manual download, 3m x62w manual free, 3m x62w manual instructions.**

A dark picture may still be incorrectly adjusted. Use a bright picture when adjusting. For a video signal or svideo signal The video format best suited for the respective input signal will be selected automatically. In such a case, remove the signal connector so that no signal is received and turn SYNC ON G off, and then reconnect the signal. The RESOLUTION menu will be displayed. At some signals, this function may not work well. To quit the operation, press the MENU button on the remote control MENU POSITION or keep no operation for about 10 seconds. Please move the frame to the position of the picture which you want to use. The frame may not be able to be moved for some input signals. MyScreen To start registration, press the ENTER button on the remote control. Do not mistake freezing for a malfunction 24. When no input is detected after the power on and AUTO OFF time is set to 0, the projector will be turned off after about 30 minutes passed. AUTO OFF When the time is set to 1 to 99, and when the passed time with no signal or an unsuitable signal reaches at the set time, the projector lamp will be turned off. The factory default setting is for both 1NORMAL and 2HIGH to be on. If the remote control does not function correctly set the this to either only 1 or only 2 as 18. If necessary repeat the process from 1.31. 1.33 Contact your dealer with the 10 digit Inquiring Code. Turning the MyScreen PASSWORD off will allow normal operation of both functions. Afterwards the projector will turn off every time an incorrect PIN Code is input. The projector will also turn off if there is no key input for about 5 minutes while the PIN BOX is displayed. If the Transition Detector ALARM is displayed for about 5 minutes the lamp will turn off. SECURITY This function will activate only when the projector is started after the power switch was turned off. If an incorrect PASSWORD is input the menu will close. You cannot have two devices with

the same IP ADDRESS on the same

network. http://www.kolsan.pl/kolsan_new/photos/comcast-on-demand-remote-control-manual.xml

The lamp can break with a loud bang, or burn out, if jolted or scratched, handled while hot, or worn over time. Note that each lamp has a different lifetime, and some may burst or burn out soon after you start using them. Using the lamp for long periods of time could cause the pictures darker or the color tone poor. Note that each lamp has a different lifetime, and some may burst or burn out soon after you start using them. If the liquid adheres to your body or clothes, rinse well with water immediately. If soiling is severe, dip soft cloth in water or a neutral cleaner diluted in water, and wipe lightly after wringing well. Then, wipe lightly with a soft, dry cloth. When any such message is displayed on the screen, please follow the instructions described below. If the same message is displayed after the remedy, or if a message other than the following appears, please contact your dealer or service company. Please follow the instructions within the table. If the same indication is displayed after the remedy, or if an indication other than the following is displayed, please contact your dealer or service company. After making sure that the smoke or odor has stopped, contact your dealer or service company. The MUTE function is working. Clean the lens referring to the section "Caring for the lens". The internal 3LCD technology is an innovative 3chip design that sets itself apart by delivering vibrant, true-to-life images with better color brightness and a wider color gamut. Rely on the X62W with its unparalleled blend of features and design. The memory card can be pulled out only while the card access LED Red is off. CAUTION The accompanying 802.11g wireless LAN card uses the 2.4GHz radio frequency band. 3M X62w page 4 4. 3M X62w page 5 5 1. Main functions 1. Main functions 1.1 Live Mode Project images from PC The main function of MIU Multi Information processing Unit is the Live Mode. Only alphanumeric characters and Japanese are supported.

2 Th. 3M X62w page 8 8 Followings are required for 1 projector and 1 PC connection. Multiple PC connection is described in section 4.1. 2. Equipment connection and network setting 2. Equipment connection and network setting 2.1 Required equipment preparation Projector 1 unit PC 1 set "MIU Live Viewer" installation i. 3M X62w page 9 9 2. Equipment connection and network setting 2.2 Network connection using "OneClickCommunication" function Continued e Press the Reset key on remote control. Then Reset Menu will be displayed. If it is not connected, ch. 3M X62w page 16 16 2. Equipment connection and network setting By installing SDLink11g card, PC and wireless LAN are able to communicate in both AdHoc and Infrastructure modes. Wireless LAN initial settings for the projector is as follows. If access point is used or data encryption is used, if needs t. 3M X62w page 20 20 When con. There are two types of IDs, Administrator IDs and User IDs. The following chart describes the differences between user and administrator IDs. Below are the factory default settings for administrator IDs, user IDs and passwords. Item Description. 3M X62w page 21 21 2. Equipment connection and network setting Refer to the following for con. Any administrator only functions will not be displayed when using a user ID. Refer to the descriptions in each table. Displays the projector's current network con. IP Configuration Configures network settings. DHCP ON Enables DHCP. DHCP OFF Disables DHCP. When the configuration settings are changed, you must restart the network connection. The network connection must be restarted when the con. Item Description Cover Error Con. Mail Subject Configures the subject li. 3M X62w page 29 29 2. Equipment connection and network setting 2.5.5 Alert Settings Continued Item Description Lamp Time Error Con. Mail Subject Configures the. 3M X62w page 30 30 2. Equipment connection and network setting 2.5.

<http://www.drupalitalia.org/node/68350>

5 Alert Settings Continued Item Description Other Error Con. Mail Subject Configures the subject. 3M X62w page 31 31 2. Equipment connection and network setting 2.5.5 Alert Settings Continued Item Description Filter Time Alarm Con. Item Description Daily Con. Schedule List Displays the current

daily schedule. Sunday Configures the Sunday schedule. Schedule Click th. 3M X62w page 33 33 2. Equipment connection and network setting 2.5.6 Schedule Setting Continued Item Description Speci.Command Configures the commands to be executed. Power Parameter Con.Cycle Configures. 3M X62w page 36 36 2. Equipment connection and network setting 2.5.8 Security Settings Item Description Administrator authority Con.Administrator ID Con.The length of the text can be up to 32 alphanumeric characters. Administrator Password Con. Authentication Password Con.The length of the text can be up to 16 alphanumeric characters. Select an item using the up and down arrow keys on the PC. Most of the items have a submenu. Refer to the table below for details. Controls the projector. Item Description Main Power Turns. 3M X62w page 39 39 2. Equipment connection and network setting 2.5.9 Projector Control Continued Item Description Image Aspect Selects the Aspect setting. Over Scan Selects the Over Scan setting. V Position Adjusts the V Position. H Position Adjusts the H Position. H Phase Adjusts the H Phase. H Size Adjusts the H Size. Auto Adjust Performs Auto Adjustment. 2.5. 3M X62w page 40 40 2. Equipment connection and network setting Language Selects the Language for the OSD. Menu Position V Adjusts the vertical Menu Position. Menu Position H Adjusts the horizontal Menu Position. Blank Selects the Blank mode. Startup Selects the Startup screen mode. Item Description Restart Restarts the projector's network connection in order to activate new con.Following window appears as s. 3M X62w page 43 43 2.

<http://www.compustoneinc.com/images/canon-lide-30-manual.pdf>

6 Utilize Web Remote Control Continued Click "Remote Control" in this window to display Web Remote Control as shown in g.2.6.b. The same operation as the bundled remote control will done. Then that is compressed as JPEG and sent to projector. By control bar in this tab, you can set compression rate. Low At the far left, Low picture quality Make JPEG compression rate high. Check the IP address in PCs and confirm xxx of. 3M X62w page 56 56 "PCLESS Presentation" reads image data from memory cards inserted into SD or USB slot and perform followings. Click the "SLIDE SHOW" button in Web Remote Control, then Slide show will be played. Select "SLIDE SHOW" on PCLESS PRESENT A TION Menu. Then Slide show will start. You can play the Slide show at your desired con guration. C. 3M X62w page 63 63 4.2.4 Directory display Directory display Fig.4.2.4 shows saved directories and.Click the "DIRECTOR Y" button in the Web Remote Control, then the directory tree will be displayed. While displaying directory, preview picture of selected. Select "DIRECTOR Y" in PCLESS PRESENT A TION Menu.Example If the IP address of the projector is set to 192.168.1.10 There are three types of scheduling. 1 Daily Perform the speci.Communication P or t The following two ports are assigned for the command control. The reply data format is the same as the RS232C commands. However, the following reply will be sent back in the event of authentication failure when authentication is enabled. 3M X62w page 78 78 Reply Data f or mat The connection ID the data is same as the connection ID data on the sending data format is attached to the RS232C commands reply data. Reply Connection ID 0x06 1 byte Reply Connection ID 0x15 1 byte Reply Error code Connection ID 0x1C 2 bytes 1 byte. 3M X62w page 79 79 Automatic Connection Break The TCP connection will be automatically disconnected after there is no communication for 30 seconds after being established.

<http://condit-pack.com/images/canon-lide-500f-manual.pdf>

Authentication The projector does not accept commands without authentication success when authentication is enabled. The projector uses a challenge response type authentication with an MD5 Mes. 3M X62w page 80 80 5. Troubleshooting 5. Troubleshooting 5. Troubleshooting Problem Likely Cause Things to Check Reference Page Number No image The projector is not turned on.If this does not resolve the problem, contact your dealer or service company. They wil. 3M X62w page 84 Intended Use Before operating this machine, please read this entire manual thor ough ly. The 3M TM Multimedia Projectors are designed, built, and tested for use indoors, using 3M lamps, 3M ceiling mount hardware, and nominal local voltages. The use of other replacement lamps, outdoor

operation, or different voltages has not been tested and could. Please check your inbox, and if you can't find it, check your spam folder to make sure it didn't end up there. Please also check your spam folder. After reading them, store them in a safe place for future reference. The memory card can be pulled out only while the card access LED Red is off. You do not need a radio license to use this card, but you should be aware of the following. In particular, please be aware that using the wireless LAN card in locations where there is reinforced steel, other metals and concrete may interfere with radio communication. Please refer to the following table for confirming where and with what channels you may use the accompanying 802.11g wireless LAN card. Please consult with your dealer for countries not included in the table. On Live Mode, the projector displays the screen appearing on the PC via network, supported by "MIU Live Viewer" Fig.1.1.a. Multiple PC connection is described in section 4.1. To eliminate communication problems, please procure a WiFi certified wireless LAN card. This function makes PC and projector network connection very easy without complicated settings like IP address and SSID.

If Easy Menu is displayed, change the menu to Advanced menu. Then Reset Menu will be displayed. Window appears in g. 2.2.a. Refer to section 3.1 how to use "MIU Live Viewer". Next section explains PC settings. This is the end of Equipments connection. IP address 192.168.1.10 Subnet mask 255.255.255.0 In this case, projector has "192.168.1.10" IP address, specify from 1 to 254 except 10 for PC. Server that has DHCP function is called DHCP server. Contact network administrator in detail. If it is not connected, check cable connections and settings are properly or not. If certain quantities of equipments are used, this mode is efficiently. Wireless LAN initial settings for the projector is as follows. Set IP address and other settings as same as wired LAN connection set up. 12 Network name SSID wireless If access point is used or data encryption is used, it needs to change settings properly. Refer to PC or wireless LAN device user guide for detailed information. See the Help files for your web browser for details on how to enable JavaScript. Please Re-log on to continue operations via a web browser. Please do not close this small, blank window. If this window is closed, the system will automatically log off after certain period of time even if an operation is being performed. It is especially recommended that all users running Internet Explorer on a Microsoft Windows version prior to Windows XP Service Pack 2 install security update Q832894 MS04004 or the web browser interface may not be displayed correctly. There are two types of IDs, Administrator IDs and User IDs. The following chart describes the differences between user and administrator IDs. Example If the IP address of the projector is set to 192.168.1.10 Any administrator only functions will not be displayed when using a user ID. Refer to the descriptions in each table. This information is In addition, depending on the Available number of input characters The length of.

www.goataxiservice.com/wp-content/plugins/formcraft/file-upload/server/content/files/1626be5a60d4d9---compustar-9000-manual.pdf

We delete comments that violate our policy, which we encourage you to read. Discussion threads can be closed at any time at our discretion. Post your question here in this forum. We're committed to dealing with such abuse according to the laws in your country of residence. When you submit a report, we'll investigate it and take the appropriate action. We'll get back to you only if we require additional details or have more information to share. Note that email addresses and full names are not considered private information. Please mention this; Therefore, avoid filling in personal details. Please enter your email address. Alternatively, choose a bare bulb without housing if you already have experience with replacing bare bulbs and are willing to deal with the more challenging replacement process. If you do not want to compromise on projection quality and reliability, choose an original manufacturer lamp. If you prefer a cheaper option and projection quality and reliability are not your top priority, buy a generic lamp. A suitable compromise is the original bulb inside option. It provides the same projection quality as an original manufacturer lamp, yet for a better

price. You can choose from 3 lamp options original, hybrid or generic. This option is recommended for its maximum reliability and easy replacement process. This is a very reliable solution and is cheaper than the original manufacturer option. We recommend it thank to its reliability and affordable price. This is a very reliable solution and is cheaper than the original manufacturer option. We recommend it thank to its reliability and affordable price. It is a cheaper solution recommended for inhome use, where projection quality and reliability are not as crucial. Even though generic lamps are not necessarily of the same quality as original manufacturer lamps, their price is nevertheless very attractive. You can choose from two options of this bare lamp original or generic.

This solution is cheaper than a lamp with housing, although it requires a certain amount of manual skills. This option is recommended for customers who already have some experience with bare bulb replacement. Keep in mind that replacing the bulb in the housing requires manual skills and tools. It is the cheapest option which we recommend for inhome use, where projection quality and reliability are not as crucial. Even though generic bulbs are not necessarily of the same quality as original manufacturer bulbs, their price nevertheless is very attractive. Which one should I choose We will help you find the right lamp Please provide us with your contact details below. We will immediately find out for you exactly when the product should be available, so you can place your order accordingly. Please try again. Please try your search again later. You can edit your question or post anyway. If you are a seller for this product, would you like to suggest updates through seller support Amazon calculates a products star ratings based on a machine learned model instead of a raw data average. The model takes into account factors including the age of a rating, whether the ratings are from verified purchasers and factors that establish reviewer trustworthiness. If you want NextDay, we can save the other items for later. Order by, and we can deliver your NextDay items by. You won't get NextDay delivery on this order because your cart contains items that aren't "NextDay eligible". In your cart, save the other items for later in order to get NextDay delivery. Oops! There was a problem with saving your items for later. You can go to cart and save for later there. Ask a question Ask a question If you would like to share feedback with us about pricing, delivery or other customer service issues, please contact customer service directly. So if you find a current lower price from an online retailer on an identical, instock product, tell us and well match it.

See more details at Online Price Match. All Rights Reserved. To ensure we are able to help you as best we can, please include your reference number Feedback Thank you for signing up. You will receive an email shortly at Here at Walmart.com, we are committed to protecting your privacy. Your email address will never be sold or distributed to a third party for any reason. For immediate help, please contact Customer Care. Thank you Your feedback helps us make Walmart shopping better for millions of customers. OK Thank you! Your feedback helps us make Walmart shopping better for millions of customers. Sorry. We're having technical issues, but we'll be back in a flash. Done. If you order a projector lamp from our company and you are not satisfied for any reason, you may send the projector lamp back for a full refund or an exchange. If you order a projector lamp from our company and you are not satisfied for any reason, you may send the projector lamp back for a full refund or an exchange.

<http://www.drupalitalia.org/node/68351>